

If your software was provided with a hardware key (USB or Parallel device), additional installation steps are required. The additional steps are as follows:

#### USB Key:

An installation file is contained in the "\USBKey" directory of the GASWorkS installation CD. Using Windows Explorer, find and double click on the "usbkeysetup.exe" file. The setup program will self extract and begin execution.

- 1) When the Welcome Screen is displayed, select Next to continue.
- 2) When the License Agreement is displayed, review the terms and either accept or decline the terms. Select Next to continue.
- 3) When the Destination screen is displayed, select Next to continue.
- 4) When the Setup Type screen is displayed, select the "Complete" option, then select next to continue.
- 5) When the Ready To Install screen is displayed, select the Install to continue.
- 6) A message will appear when the installation is complete, review the message, then select Finish to complete the installation.

#### Printer Port Key:

If the operating system is Windows 98 or ME no additional installation is required. If the operating system is Windows NT based (NT, XP, or 2000), the system driver for the hardware key needs to manually installed. The ntdrvr.exe file contained in the "\NTPatch" directory of the GASWorkS installation CD is a self extracting file that contains the required installation program. Copy the file to a temporary directory on your hard disk. Unzip it by double clicking on it using Windows Explorer. After unzipping the file, follow the directions found in the readme.txt file, or use the following instructions:

- 1) Close the Zip utility screen.
- 2) Go to the win\_nt directory.
- 3) Double click on the setupx86.exe file.
- 4) From the Functions menu, select Install Sentinel Driver item.
- 5) Close the Setup screen

After the driver has been installed, you can delete the temporary directory and files if you want.